

PIETRA SERIES

125-135 Bonds Rd Riverwood NSW 2210, AUSTRALIA | T +61 2 9584 4000 | W www.aceceramics.com.au | E sales@aceceramics.com.au

 **aceceramics**
beyond our customer's expectations since 1974

PIETRA resembles natural stone with characteristic white veining throughout. Four natural colour ways make this a versatile series



PRODUCT TYPE: Glazed porcelain

COLOURS: Ice, Sand, Wind Silver and Shell Charcoal

SIZES: 300x300mm, 300x600mm, 600x600mm
and 450x900mm
Rectified Edges

FINISHES/USAGE:

Matt, Lappato and Grip/Wall and Floor

AESTHETIC QUALITIES:

Marble, Stone vein look


ORIGIN:

N/A

TECHNICAL DATA:

P3 Pendulum slip rating (Matt)
P4 Pendulum slip rating (Grip)
More technical data on last page

VARIATION:



V3

Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

PIETRA SERIES

125-135 Bonds Rd Riverwood NSW 2210, AUSTRALIA | T +61 2 9584 4000 | W www.aceceramics.com.au | E sales@aceceramics.com.au



beyond our customer's expectations since 1974

PRODUCT INFORMATION



Ice

Matt	300x300mm 300x600mm 600x600mm
Lappato	300x600mm 600x600mm
Grip	300x600mm



Wind Silver

Matt	300x300mm 300x600mm 600x600mm 450x450mm
Lappato	300x600mm 600x600mm
Grip	300x600mm



Sand

Matt	300x300mm 300x600mm 600x600mm
Lappato	300x600mm 600x600mm
Grip	300x600mm



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

PIETRA SERIES

125-135 Bonds Rd Riverwood NSW 2210, AUSTRALIA | T +61 2 9584 4000 | W www.aceceramics.com.au | E sales@aceceramics.com.au

 **aceceramics**
beyond our customer's expectations since 1974

LIFESTYLE IMAGES



Variation is an inherent property of tiles and stone. Sizes are nominal and may include a joint.

PIETRA SERIES

125-135 Bonds Rd Riverwood NSW 2210, AUSTRALIA | T +61 2 9584 4000 | W www.aceceramics.com.au | E sales@aceceramics.com.au



TECHNICAL DATA

technical characteristics	test method	required values	value
water absorption	iso 10545-3	$0,5\% < E \leq 3\%$	-
breaking strength (S)	iso 10545-4	$\geq 1300 \text{ N}$	pass
thermal shock resistance	iso 10545-9	no visible defects	pass
chemical resistance	iso 10545-13	Class A	pass
length and width of the average sizes	iso 10545-2	$\pm 0,5\%$	pass
thickness	iso 10545-2	$\pm 0,5\%$	pass
straightness of sides	iso 10545-2	$\pm 0,5\%$ and $\pm 1.5\text{mm}$	pass
surface quality	iso 10545-2	minimum of 95% of tiles free from visible defects	pass